

(19)

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 738 998 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
23.10.1996 Bulletin 1996/43

(51) Int Cl.⁶: G09G 3/36

(21) Application number: 96302630.7

(22) Date of filing: 16.04.1996

(84) Designated Contracting States:
DE FR GB IT NL

(30) Priority: 20.04.1995 JP 95505/95

(71) Applicant: CANON KABUSHIKI KAISHA
Tokyo (JP)

(72) Inventors:
• Mori, Hideo
Tokyo (JP)
• Yokomizo, Hiroyuki
Tokyo (JP)

• Takahashi, Masanori
Tokyo (JP)
• Niibori, Kenji
Tokyo (JP)
• Ohsawa, Seiji
Tokyo (JP)


(74) Representative:
Beresford, Keith Denis Lewis et al
BERESFORD & Co.
2-5 Warwick Court
High Holborn
London WC1R 5DJ (GB)

(54) Display apparatus and assembly of its driving circuit

(57) A display apparatus and an assembly of a driving circuit for the display apparatus having a display device, a film carrier with a lead to transfer a signal for driving the display device, and a bus board to supply a signal to the lead. A dummy lead is provided along the outside

of each of an input side outer lead and an output side outer lead of the film carrier. A predetermined voltage is applied to the dummy leads. The predetermined voltage value is set to a value so as not to stationarily cause a DC bias for the voltage of the outer lead on the outside.

FIG.1A



Description

BACKGROUND OF THE INVENTION

Field of the Invention

The invention relates to a display apparatus which is used for a television receiver, a view finder of a video camera, a light bulb of a video projector, a display of a computer, or the like and, more particularly, to an assembly of a driving circuit of such a display apparatus.

Related Background Art

As a recent display apparatus, attention is paid to a display apparatus having a display device such as liquid crystal device, plasma light emitting device, electrochromic device, electron emitting device, or the like in place of a CRT.

Each of those display devices has a number of pixels and has an electrode to apply an electric signal to decide an optical state of each pixel.

Further, in order to apply the electric signal to the electrode of the display device, a rigid wiring board called a bus board or a driver board and made of glass epoxy or the like and a flexible wiring board such as a TAB film or the like are used.

Such a structure has been disclosed in U.S.P. 5,019,201 or 5,360,943 or the like.

A case where a liquid crystal display panel is used as a display device and a film carrier having a driving IC chip is used as a flexible wiring board will now be described hereinbelow.

Hitherto, in case of connecting the film carrier on which a driving circuit is mounted to a display panel and a bus board, there is a drawback such that outer leads locating at both ends among the outer leads on the input side and output side are likely to be damaged by a stress from the outside due to a shock, a vibration, a thermal stress, or the like.

To solve such a drawback, therefore, as shown in Fig. 6, dummy leads 8 and 9 which are electrically not related to the driving for an image display are arranged on both outsides of outer leads 6 and 5 on the input side and output side among the leads of the film carrier, thereby preventing a damage of the outer leads at both ends due to an external stress. In Fig. 6, reference numeral 1 denotes a display panel; 2 a driving circuit such as an IC chip or the like; 3 a bus board; 4 a film carrier; and 7 a soldering land for the dummy leads.

There is a case where a quality of an image which is displayed in a display area is improved by always holding the outside of the display area to display the image to either one of a white state (bright state) and a black state (dark state). Such a method is called a frame driving.

Fig. 7 shows an example of a display apparatus. Four electrodes 99 for a frame driving are provided for

the display panel 1 and are connected to leads for a frame driving of film carriers 4 and 4' arranged at both ends of two bus boards 3. Reference numerals 201 and 201' denote scanning line driving circuits of the film carriers 4 and 4'.

One of methods for the frame driving is a method whereby film carriers and driving circuits of substantially the same construction are used as all of the film carriers 4 and 4' and all of the driving circuits 201 and 201' and the apparatus is driven so as to supply a signal for always holding the pixels (frame pixels) on the electrodes 99 for the frame driving in a white or black state to the electrodes 99.

Another method is a method invented by the present inventors et al., namely, a method whereby the structure of the film carriers 4' at both ends of the bus board 3 is made different from a structure of the other film carriers 4.

Fig. 8 shows a structure of the film carrier 4' which is used in such another method.

It is also possible to construct in a manner such that an input side and an output side of dummy leads 8' and 9' are electrically short-circuited and connected in order to supply a signal for, for example, always displaying in white to the frame driving electrodes 99 on the outside of a display area of the display panel 1, the input side is connected to the bus board 3, and the output side is connected to the terminal of the frame driving electrodes of the display apparatus, thereby directly supplying the signal from the bus board 3 to the display apparatus without passing through the driving circuit 201' and driving a frame area.

In case of the above structure, the same IC chip as that of another driving circuit 201 can be used as a driving circuit 201'.

There is no need to give a special construction or special driving control for a frame driving to the IC chip.

In case of a structure shown in Fig. 6, since the dummy lead 9 electrically enters a floating state, it functions as a role of an antenna and radiation noises are generated.

To avoid such a problem, when the dummy leads 8 and 9 are short-circuited to the adjacent outer lead 5, the dummy leads 8 and 9 cannot be used for the frame driving of the display panel 1.

In the case where, for example, the dummy leads 8 and 9 are held to a ground and are fixed to a grounding voltage in order to avoid the electrical floating state, a stationary DC voltage difference occurs between the dummy leads 8 and 9 and the outer leads 5 and 6 which are adjacent thereto. At this time, particularly, in a connecting portion between the display panel 1 and the outer lead 9 on the output side, a failure such as disconnection or the like due to an electric corrosion is likely to be caused.

SUMMARY OF THE INVENTION

It is an object of the invention to provide a display apparatus without an erroneous operation due to noises.

Another object of the invention is to provide a display apparatus having an assembly of a driving circuit which can be also applied to a display panel which needs a frame driving.

Still another object of the invention is to provide a display apparatus in which disconnection is hardly caused due to an electric corrosion.

Further another object of the invention is to provide a display apparatus having an assembly of a driving circuit in which a generality is high and costs are low.

The invention is made in consideration of the above circumstances and there are provided a display apparatus comprising a display device, a driving circuit mounted on a film carrier to drive the display device, and a bus board to supply a power source and a signal to the driving circuit and an assembly of a driving circuit of such a display apparatus, wherein a dummy lead is provided along the outside of each of an outer lead on the input side and an outer lead on the output side of the film carrier, and a predetermined voltage is applied to the dummy leads.

In this case, the predetermined voltage value which is applied to the dummy leads is selected to a value such as not to stationarily apply a DC bias to the voltage of the outer lead on the output side.

One end of the dummy lead is connected to a bus board and the other end is connected to the display apparatus.

According to the invention, by setting the voltage of the dummy lead to a value such as not to apply the DC bias as much as possible for a voltage waveform of the outer lead on the output side, the movement of ions in a connecting portion between the outer lead and the display apparatus can be suppressed and a failure such as a disconnection or the like due to an electric corrosion can be prevented.

Since the dummy lead is not in the electrical floating state, there is no fear of radiation noises from the dummy lead.

On the other hand, since the dummy leads on the input side and the output side are common, by arbitrarily setting the voltage to be applied to a land for the dummy lead on the input side, a voltage can be also directly applied to the display apparatus through the film carrier.

BRIEF DESCRIPTION OF THE DRAWINGS

Figs. 1A to 1C are diagrams showing an assembly according to the first embodiment of the invention; Fig. 2 is a diagram showing voltage waveforms according to the first embodiment of the invention; Fig. 3 is a diagram showing voltage waveforms according to the second embodiment of the invention;

Fig. 4 is a diagram showing an assembly of the second embodiment of the invention;

Fig. 5 is a diagram showing a control system of a display apparatus of the invention;

Fig. 6 is a diagram showing a conventional assembly;

Fig. 7 is a diagram showing a conventional display apparatus;

Fig. 8 is a diagram showing an example of an assembly; and

Fig. 9 is a diagram showing a comparison of voltage waveforms of the display apparatus.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1A is a plan view showing an assembly of a driving circuit according to a preferred embodiment of the invention. Fig. 1B is a cross sectional view taken along the line 1B-1B in Fig. 1A. Fig. 1C is a cross sectional view taken along the line 1C-1C in Fig. 1A.

The structure of Fig. 1A can be used in place of all of the film carriers 201 and 201' in the diagrams.

Reference numeral 1 denotes the display panel as a display device. The display panel 1 has a number of pixels. Reference numeral 2 denotes the IC chip as a driving circuit; 3 the bus board; 4 the film carrier; 5 the outer lead on the output side; 6 the outer lead on the input side; 8 the dummy lead on the input side; 9 the dummy lead on the output side; 16 a soldering land as a connecting terminal on the bus board side; 18 a soldering land for the dummy lead; and 15 an electrode of the display panel. The electrodes 15 are connected as scanning electrodes or information electrodes to the pixels.

Reference numeral 19 denotes a dummy lead of the display panel. In case of performing the frame driving, the dummy lead 19 functions as an electrode for the frame driving and is extended into the display panel. However, in the other cases, the dummy lead 19 is not extended as shown in Fig. 1A. AD denotes a connecting member such as soldering, anisotropic conductive adhesive agent, or the like.

The driving circuit 2 applies a voltage necessary for driving the display panel 1 to the display panel 1 through the outer lead 5 on the output side. Such a voltage supply is performed on the basis of a power source and a signal which were supplied from the group of input side outer leads 6 electrically connected to the bus board 3.

The voltage that is applied to the display panel 1 through the output side outer lead 5 in this instance is shown in Fig. 2.

In case of using the driving circuit 2 as a circuit for driving the scanning electrodes, a waveform A in Fig. 2 is time-sequentially outputted to the driving electrodes 15. In case of using the driving circuit 2 as a circuit for driving the information electrodes, a waveform B in Fig. 2 according to an image to be displayed is outputted to

the driving electrodes 15. A reference voltage VC is applied to the dummy electrode 19 of the display panel 1 from the land 18 of the wiring of the bus board without passing through the driving circuit 2.

When the scanning side waveform shown as a voltage waveform example A of the outer lead 5 on the output side is seen with respect to only a period within the period of time shown in Fig. 2, although its average voltage is a plus voltage, a duty of the scanning side waveform is small and is equal to or less than 1/400. Therefore, it can be regarded as almost zero DC voltage for the reference voltage VC when it is seen as a voltage in, for example, one frame period. In the information side waveform example shown as a voltage waveform example B of the output side outer lead, an average voltage value in one horizontal scanning period is equal to zero for VC.

The dummy lead 9 on the output side is electrically connected to the dummy lead 8 on the input side and the dummy lead on the input side is connected to the land 7 for the dummy lead on the bus board 3 by soldering, so that the voltage of the output side dummy lead 9 can be arbitrarily set.

At this time, for example, assuming that the voltage of the output side dummy lead 9 is set to VC as shown in Fig. 2, a voltage difference between the output side dummy lead 9 and the output side outer lead (in case of an example on the information side) on the outermost side that is adjacent to the dummy lead 9 is equal to zero as a DC level at least in one horizontal scanning period. An instantaneous voltage difference is also equal to $IV_+ - VCI$ at most, the movement of ions can be suppressed to a low level. Thus, a leading electrodes of the display panel 1 made of a thin metal (for example, aluminum) film having a thickness within a range from hundreds of Å to thousands of Å can be protected from a damage due to an electric corrosion.

A case where, for example, a voltage waveform shown in Fig. 3 is applied to the output side dummy lead will now be described.

That is, it is used for applying to the electrodes 99 in what is called a frame driving area arranged on the outside of a display area of the display panel 1 as shown in Fig. 4 through the dummy lead 9 arranged on the panel outside of the driver IC 201' on the outermost side in the group of driver ICs 2 mounted on, for instance, a TAB film shown in Fig. 7 and for always fixing the frame driving portion to a white display or a black display.

At this time, an alternating voltage difference whose DC component is equal to zero is caused between the output side dummy lead 9 and the output side outer lead (corresponding to the electrode on the information side) on the outermost side that is adjacent to the dummy lead 9 only for one horizontal scanning period during which the voltage for the frame driving is applied. For the other period of time in one frame, even an alternating voltage difference doesn't occur between the dummy lead and the outer lead and the DC component is equal to zero

and a DC level is equal to zero. The instantaneous voltage difference is equal to $2IV_+ - VCI$ at most. When it is compared with the case where the voltage of the output side dummy lead is fixed to VC, although the voltage difference is larger, its level is almost equal to a voltage difference between the output side outer leads. The output side dummy lead portion is not weak particularly for the electric corrosion.

In each of embodiments shown in the diagrams, the voltage which is applied to the dummy electrode of the display panel or the electrode for the frame driving through the dummy lead has been directly supplied to the display panel from the bus board through the film carrier without passing through the driver IC. However, a form in which such a voltage is applied through the driver IC can be also used.

In case of the form of applying the voltage through the driver IC, since the number of terminals of the driver IC increases, the form shown in the diagram is more preferable in an apparatus which preferentially intends to realize low costs.

The driver IC is not necessarily the film carrier package IC but may be also a driver IC provided as a COG (chip-on-glass) on the display panel.

It is sufficient not to cause a DC component in the voltage difference between the dummy lead and the lead adjacent thereto for a period of time longer than one horizontal scanning period. However, it is preferable that there is no DC component in one horizontal scanning period. It is, therefore, sufficient to decide a voltage to be applied to the dummy lead so as to eliminate the DC component.

As the number of dummy leads, it is sufficient that at least one dummy lead is provided on each of the right and left sides of the group of outer leads per one film carrier. More preferably, two to four dummy leads are arranged on each of the left and right sides.

As a display panel which is used in the invention, a liquid crystal device, a plasma light emitting device, an electrochromic device, an electron emitting device, or the like can be mentioned. Particularly, the invention is effective for a non-active matrix type device using a chiral smectic liquid crystal or a chiral nematic liquid crystal or an active matrix type device using a TN liquid crystal.

An image display apparatus using the liquid crystal devices in the embodiments described above will now be explained.

Fig. 5 is a block diagram of a control system of the image display apparatus. Reference numeral 200 denotes a display panel in which a polarization plate is combined to the foregoing liquid crystal device and which has a back light source as necessary. Reference numeral 201 denotes the scanning line driving circuit including a decoder and a switch; 202 an information line driving circuit including a latch circuit, a shift register, a switch, and the like; 203 a voltage generating circuit for generating a number of reference voltages which are supplied to both of the driving circuits 201 and 202; 204

a control circuit which includes a CPU and an RAM to store image information and outputs signals to be supplied to the outer lead and the dummy lead; and 210 an image signal source such as image sensor for inputting an image, computer which executes an application program, or the like.

The invention is applied to an assembly with at least any one of the display panel 200, scanning line driving circuit 201, and information line driving circuit 202.

As compared with the case where the output side dummy lead 9 is fixed to the GND level as shown in Fig. 9, a fact that the apparatus of the invention is strong several times for the electric corrosion has been confirmed by the following reliability tests.

As for the structure of Fig. 6, a pitch of the output side outer leads (= leading electrode pitch of the display panel) is set to 100 μm and a leading electrode construction is formed by the electrodes in which ITO (1000 \AA) and aluminum (3000 \AA) are laminated on a soda glass. VC is set to 20 V, V_+ is set to 26 V, and V_- is set to 14 V. Under an environment of 45°C/95 %RH, the output side dummy lead is fixed to the GND voltage and driven as in the conventional apparatus shown in Fig. 9. In this case, a disconnection due to the electric corrosion occurs in the leading electrode portion connected to the output side dummy lead 9 and in the leading electrode portion adjacent to the above leading electrode after the elapse of 168 hours. On the other hand, in the case where the output side dummy lead is fixed to the VC voltage and is driven as shown in Fig. 2, it has been confirmed that no failure due to the electric corrosion occurs even after the elapse of 1000 hours.

As described above, according to the invention, the input side dummy lead and the output side dummy lead of the film carrier on which the driving circuit is mounted are commonly constructed and the voltage of the dummy lead is set to be almost zero for the voltage waveform of the output side outer lead, so that the movement of ions in the connecting portion of the outer lead and the display apparatus can be suppressed. The failure such as a disconnection due to the electric corrosion or the like can be prevented.

Since the dummy lead is not in the electrical floating state, there is no fear of radiation noises from the dummy lead.

On the other hand, since the input side dummy lead and the output side dummy lead are commonly constructed, by arbitrarily setting the voltage to be applied to the land for the input side dummy lead, the voltage can be also directly applied to the display panel without passing through the film carrier.

Claims

1. An assembly of a driving circuit for a display apparatus comprising a display device, a film carrier having a lead to transfer a signal for driving said display

device, and a bus board for supplying a signal to said lead, wherein

a dummy lead is provided along the outside of each of an input side outer lead and an output side outer lead of said film carrier, and a predetermined voltage is applied to said dummy leads.

2. An assembly according to claim 1, wherein said predetermined voltage value which is applied to said dummy lead is set to a value that is decided so as not to stationarily cause a DC bias for a voltage of said output side outer lead.

3. An assembly according to claim 1, wherein one end of said dummy lead is electrically connected to said bus board and the other end is electrically connected to said display device.

4. A display apparatus comprising:

a display device having a group of electrodes for supplying signals to pixels;

a bus for transferring the signals which are supplied to said group of electrodes or signals to drive said electrodes; and

a film carrier having a group of leads for electrically connecting said group of electrodes of said display device and connecting terminals of a bus board;

wherein said film carrier has dummy leads on both sides of said group of leads, and a DC component of a voltage difference which is caused between said dummy lead and a lead adjacent to said dummy lead is almost equal to zero in a predetermined period of time.

5. An apparatus according to claim 4, wherein voltages (V_+ , V_-) of both polarities for a center voltage (VC) are applied to said group of electrodes, and a voltage of the same potential as said center voltage is applied to said dummy leads.

6. An apparatus according to claim 4, wherein a scanning non-selection voltage (VC) and scanning selection voltages (V_+ , V_-) are applied to said group of electrodes, and a voltage of the same potential as said scanning non-selection voltage is applied to said dummy leads.

7. An apparatus according to claim 4, wherein a signal is supplied to said dummy leads for a predetermined period of time and said dummy lead is held at a predetermined voltage for a period of time other than said predetermined period of time.

8. An apparatus according to claim 4, wherein a voltage for a frame driving is applied to at least one of said dummy leads.

9. An apparatus according to claim 4, wherein said film carrier has a driver IC.
10. An apparatus according to claim 4, wherein said dummy leads and a dummy electrode of said display device are electrically connected. 5
11. An apparatus according to claim 4, wherein said dummy leads and a dummy electrode or an electrode for a frame driving of said display device are adhered by an anisotropic conductive adhesive agent. 10
12. An apparatus according to claim 4, wherein said dummy lead is held at a predetermined voltage for at least one frame period of time. 15
13. An apparatus according to claim 4, wherein said dummy leads are held at a predetermined voltage for at least one frame period of time. 20
14. An apparatus according to claim 4, wherein said film carrier has an input side outer lead that is connected to said bus board, an output side outer lead that is connected to said display device, and a dummy lead for short-circuiting said bus board and said dummy electrode or said electrode for the frame driving of said display device. 25
15. An apparatus according to claim 14, wherein said input side outer lead and said output side outer lead are connected to a driver IC, and said dummy lead is not connected to said driver IC. 30
16. An apparatus according to claim 4, wherein said display device is any one of a liquid crystal device, a plasma device, an electrochromic device, and an electron emitting device. 35
17. An apparatus according to claim 4, wherein said predetermined period of time is longer than one horizontal selection period of time. 40
18. An apparatus according to claim 4, wherein said predetermined period of time is one frame period of time. 45

50

55

A schematic diagram of an elongated member 16, which is segmented. It consists of a series of segments 8 connected by joints 18. The member is shown in a perspective view, with a central segment 8 and several joints 18. The segments 8 are labeled with the number 8, and the joints 18 are labeled with the number 18. The entire assembly is labeled with the number 16. A label AD is also present near the right end of the member.

FIG.2




FIG.3




FIG.4




FIG.5




FIG.6




FIG.7




FIG.8





FIG.9





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 96 30 2630

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	EP-A-0 601 869 (KABUSHIKI KAISHA TOSHIBA) 15 June 1994 * column 25, line 20 - column 25, line 45; figure 18 *	1,3,4,9, 14-16	G09G3/36
A	US-A-5 285 301 (KAZUO SHIRAHASHI) 8 February 1994 * abstract; figure 15 *	10,11	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			G09G G02F
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 7 August 1996	Examiner Van Roost, L
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.82 (P04.001)